Raley settings reference - server

Setting	Description	Example
outgoing_email.from_address	Overrides default Jira's outgoing SMTP server from address in outgoing emails. Can be customized as per project level using this notation: outgoing_email.from_address.ABC Where ABC is your Jira project key for which you override from address	outgoing_email.from_address=support@mycompany.com outgoing_email.from_address.ABC=supportabc@mycompany.com
outgoing_email.from_name	Overrides default Jira's outgoing SMTP server from name in outgoing emails Can be customized as per project level using this notation: outgoing_email.from_name.ABC Where ABC is your Jira project key for which you override from address	outgoing_email.from_name=Jack Smith outgoing_email.from_name.ABC=John Dough
show_addon_to_pa	If set to "true" then Raley Emails Notifications will be visible to Jira users with role Project Admin. Otherwise, the add-on is only visible to Jira admins and sysadmins	show_addon_to_pa=true
EVENT_PROCESSING_DELAY	Delays processing of Jira/JSM events by Raley by specified number of seconds. By default, there's no delay and events are processed as soon as possible.	EVENT_PROCESSING_DELAY=15
APPLY_ISSUE_FORCE_STORE	Makes a call to MutableIssue.store() function before proceeding with evaluation of notifications configurations. Sometimes this is useful to ensure that the issue is in the right state so it will match expected Raley notification configuration conditions. By default, no call to MutableIssue.store() is made	APPLY_ISSUE_FORCE_STORE=true